

# ANHUI JANTLE MARINE ENGINEERING CO., LTD

## **FOR THE SUPPLY OF:**

## **4000HP Harbor Tug (**DAIHATSU + Rolls-Royce)









ISSUED DATE: Feb.28th, 2019



### ANHUI JANTLE MARINE ENGINEERING CO., LTD

### **SPECIFICATION**

1. Main Particulars:

Length Overall:33.98mBeam Moulded:10.00 mDepth Moulded:4.50 mMax Draft:3.40mSpeed:13.0Knots

**Bollard Pull:** Pull Ahead Max. 50T, Pull Aft Max. 42T **Endurance:** 1500 Nautical Miles @ 12.5 Knots

Accommodation: 14 Men

Fuel Oil Capacity: 80 Cubic Meters Fresh Water Capacity: 46 Cubic Meters

**GRT:** 378t

#### 2. Main Engines:

## DAIHATSU Japan

Type: 6DKM-26

Power rated: 2000PSx750rpm, 2 sets

#### 3. Propulsion:

#### **Rolls-Royce Finland**

Type: AQM US205/3000 FP, Z-drive propeller 360° maneuverability,

Power rated: 2000PSx750rpm, 2 sets

#### 4.Generator sets:

#### SHANGHAI HENGJIN POWER TECHNOLOGY CO., LTD

Power rated: 80 kW, 400V 3-wire, 2 sets.

**5.Anchor Windlass/Towing winch:** ( Electric-Hydraulic Driven )

MANABLE ZOKI Japan2, sets

Gypsy Wheel:  $\Phi$  24mm 3.5Tx10m/min Towing Drum: 3.0t/1.5t x 25m/50m/min

Drum Capacity:  $\phi$ 110×120m

Break Power: 60t

Anchor&Anchor Chain: anchor 2×700kg, dia 24mm.

#### 6.Towing hook:

Capacity: 60t CHINA

#### 7.. Stern Capstan:

Electric-Hydraulic Driven

Winding Load & Winding Sped: 3t×15m/min CHINA

8.Oily Water Separator: 0.25m<sup>3</sup>/hr, 1 set CHINA

#### 9. External Fi-fighting: CHINA

1 set diesel driven pump: cap.x head: 475m³/hx132m. 1 set remote monitor: cap.x head: 300m³/hx80m. 1 set hand monitor: cap.x head: 120m³/hx60m.

1 set foam system

#### 10. Navigation & Communications Equipment:

VHF: 2 sets Japan Furuno MF/HF: 1 set Japan Furuno Two-way VHF: Navico UK Ltd 2 sets Mcmurdo Ltd. SART: 1 set Magnetic Compass: 1 set Shanghai China Radar: 1 set Japan Furuno Echo Sounder: 1 set Japan Furuno GPS: Japan Furuno 1 set AIS 1 set Mcmurdo Ltd. Shanghai China elec. Map 1 set

11.Classification: CCS, coastal service tug

**12.Built year:** November, 2009